

IR Micro Office DALI2 APC.

Light management for individual rooms.




Offices are their passion. With its precision lens of 15 x 15 mm, the IR Micro Office DALI2 APC detects areas of up to 36 m². Installers love the networkable Bluetooth Mesh technology and optimal factory settings – a true mount-and-forget solution for individual rooms. If required, it is possible to limit the detection zone using the easily attachable cover clips. What's more, thanks to DALI Broadcast, DALI light management can be established quickly with up to 20 participants. Available as surface mounting, with concealed wiring or as a ceiling-recessed variant. In addition to continuous light control, the sensor has a push-button that acts as a manual override function.



Patented multi-segment lens for reliable presence detection













 professional line

 <p>Bluetooth Mesh for fast, energy-saving connections</p>	 <p>4 x 4 m quadratic presence detection with 168 switching zones</p>	 <p>Continuous light control for energy-saving and perfect working light</p>
---	--	---

Presence detector

IR Micro Office DALI2 APC



 <p>360° PIR with square detection</p>	 <p>Max. 5 m mounting height</p>	 <p>Settings adjustable via the free Steinel Connect App</p>	 <p>Push-button for manual override</p>	 <p>Bluetooth Mesh for networking and configuring</p>
 <p>DALI-2 application controller (broadcast with up to 20 participants)</p>			<p>Technical specifications</p> <p>Concealed wiring dimensions 85 x 37 mm</p> <p>Recessed ceiling dimensions 85 x 69 mm</p> <p>Surface mounting dimensions 106 x 45 mm</p> <p>Mounting height 2.00 – 5.00 m</p> <p>Mounting site Ceiling</p> <p>Application, location Indoor</p> <p>Sensor technology Infrared</p> <p>Angle of coverage 360°</p> <p>Radial and presence range 4 x 4 m</p> <p>Tangential range 6 x 6 m</p> <p>Time setting 5 secs – 60 mins</p> <p>Twilight setting 2 – 1000 lx</p> <p>Settings via Bluetooth Mesh</p> <p>IP rating IP20</p> <p>Ambient temperature 0–40 °C</p> <p>Manufacturer's warranty 5 years</p> <p>Order details</p> <p>IR MICRO Office concealed wiring 4007841 067151</p> <p>IR MICRO Office recessed ceiling 4007841 067144</p> <p>IR MICRO Office surface mounting 4007841 067137</p>	
 <p>Concealed wiring variant</p>	 <p>Recessed ceiling variant</p>	 <p>Surface mounting variant</p>		
