

IR Quattro HD DALI duo 24m.

Great solution.

Not only in the classroom.

- Getting started with intelligent lighting control
- Ideal for classrooms, conference rooms and large offices
- Infrared presence detector with 64 sqm presence detection,
- Mounting height max. 10 m
- DALI-APC for controlling up to 64 luminaires
- 2 light channels, 3 push-button inputs and 4800 switching zones
- Additional, potential-free relay
- Constant light control, teach function, optional main and ambient light
- Simple commissioning via Smart Remote app



IR Quattro HD DALI duo 24m










SMART
REMOTE
APP

Sensors

IR Quattro HD DALI duo 24m



 <p>2+1 light channels</p>	 <p>max. 10.00 m</p>	 <p>360°</p>	 <p>8 x 8 m Presence</p>	<p>Technical data Dimensions AP.....120 x 120 x 65 mm Dimensions EN.....120 x 120 x 119 mm Mains connection..... 220 – 240 V, 50/60 Hz Relay switching load..... max. 600 W LED Number of DALI devices..... 64 DALI communication..... addressable 2 groups/ broadcast Sensor type..... Infrared Mounting height2,50 – 10,00 m Angle of coverage.....360° Radial range.....8 x 8 m Tangential range20 x 20 m Presence range8 x 8 m Switching zones 4800 Twilight setting10 – 1000 lx Time setting.....5 s – 60 min. Basic light function.....Yes Basic lighting function Time.....1 – 60 Min., All night Adjustable main light.....50 – 100 % Twilight setting Teach.....Yes Constant light controlYes Protection class.....IP20 Temperature.....0 to 40°C HousingUV-resistant plastic Mounting type Ceiling</p> <p>Order details Surface-mounted 4007841 088835 Ceiling installation..... 4007841 088828 Smart Remote..... 4007841 009151</p>
<p>HD</p> <p>4800 zones</p>	 <p>10 - 1000 Lux</p>	 <p>5 sec - 60 min</p>	<p>IQ</p> <p>IQ-mode</p>	
 <p>3 push-button inputs</p>		<p>ON/ OFF</p> <p>ON/OFF Relais</p>		